

EPIC® POWERLOCK screw contacts

Contacts, tools, accessories for circular connectors

EPIC® POWERLOCK 400A screw contacts from 50 mm² up to 120 mm²

Info

Screw max. 400 A

Do not plug with crimp type (660 A)



Technical Data

Classification:

ETIM 5.0 Class-ID: EC000796

ETIM 5.0 Class-Description: Contact for industrial connectors

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® POWERLOCK screw contacts

Article number	Article designation	Version	For design
Sink - contact with M12 threaded post for POWERLOCK A1 S design, including contact retention pin			
44420241	POWERLOCK SP M12	Contact Drain, M12 Thread for cable lugs	for type A1
Source - contact with M12 threaded post for type POWERLOCK A6 S, contact retention pin included			
44420242	POWERLOCK QP M12	Lamella contact source, M12 thread for cable lug	for type A6
Source - contact screw for type POWERLOCK D6 S, contact retention pin included			
44420237	POWERLOCK QS 120	120 mm ²	for type D6
Sink - contact screw for POWERLOCK F6 S design, including contact retention pin			
44420232	POWERLOCK SS 120	120 mm ²	for type F6

Last Update (31.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16

EPIC® POWERLOCK screw contacts



Last Update (31.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16