

## EPIC® POWER LS1.5 female contacts

Contacts, tools, accessories for circular connectors

EPIC® POWER LS1.5 female contacts for size 1.5 circular connector series

### Info

All contacts are high-quality gold-plated  
Slotted contacts with external pressure spring



Reliability



Robust



Optimum strain relief



Mechanical resistance



Corrosion-resistant



Good chemical resistance

### Technical Data

Classification:

ETIM 5.0 Class-ID: EC000796

ETIM 5.0 Class-Description: Contact for industrial connectors

### Note

Photographs are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**EPIC® POWER LS1.5 female contacts**

Article number	Article designation	Version	For design
3.6 mm female contacts			
44429318	LS1.5 D BCEM 3,6MM AU 1,0-2,5	3.6mm female 1.0-2.5 mm <sup>2</sup>	for type D6, A6
44429319	LS1.5 D BCEM 3,6MM AU 2,5-4,0	3.6mm female 2.5-4.0mm <sup>2</sup>	for type D6, A6
44429320	LS1.5 D BCEM 3,6MM AU 4,0-6,0	3.6mm female 4.0-6.0mm <sup>2</sup>	for type D6, A6
44429321	LS1.5 D BCEM 3,6MM AU 6,0-10,0	3.6mm female 6.0-10.0mm <sup>2</sup>	for type D6, A6
2 mm female contacts			
44429322	LS1.5 D BCEM 2MM AU 0,25-1,0	2mm female 0.25 - 1.0 mm <sup>2</sup>	for type D6, A6
44429323	LS1.5 D BCEM 2MM AU 0,75-1,5	2mm female 0.75 - 1.5 mm <sup>2</sup>	for type D6, A6
44429324	LS1.5 D BCEM 2MM AU 1,0-2,5	2mm female crimp 1.0-2.5 mm <sup>2</sup>	for type D6, A6
44429325	LS1.5 D BCEM 2MM AU 4,0	2 mm female 4.0 mm <sup>2</sup>	for type D6, A6

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16