

EPIC® POWER LS1 female contacts

Contacts, tools, accessories for circular connectors

EPIC® POWER LS1 female contacts

Info

All contacts are high-quality gold-plated

Contacts are designed for a wide crimping range, therefore low number of variants

Only available as crimp version due to the high mechanical stress in servo applications



Reliability



Robust



Optimum strain relief



Oil-resistant



Mechanical resistance



Maximum vibration protection



Corrosion-resistant



Wide clamping range



Good chemical resistance

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® POWER LS1 female contacts

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® POWER LS1 female contacts**

Article number	Article designation	Version	For design
1mm female contacts			
74020601	M23/LS1 BCMS 1mm AU 0.14-1.0	1mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6
74200600	M23/LS1 BCMS 1mm AU 0.14-1.0	1mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6
74034501	M23/LS1 BCMD 1mm AU 0.14-1.0	1mm female hyperboloid 0.14-1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6
74034500	M23/LS1 BCMD 1mm AU 0.14-1.0	1mm female hyperboloid 0.14-1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6
2mm contacts female			
44429371	POWER LS1 D BCMF 2mm AU 0.5-2.5	2mm female spring 0.5-2.5mm ²	LS1 D6, A6
44429370	POWER LS1 D BCMF 2mm AU 0.5-2.5	2mm female spring 0.5-2.5mm ²	LS1 D6, A6
44420104	POWER LS1 D BCMD 2mm AU 4.0	2mm female hyperboloid 4mm ²	for type D6, A6
44420105	POWER LS1 D BCMD 2mm AU 4.0	2mm female hyperboloid 4mm ²	for type D6, A6
44429001	POWER LS1 BCBG 2mm 1.0-2.5 (3000) RE	2mm female crimp 1.0-2.5 mm ²	LS1 D6, A6

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® POWER LS1 female contacts



Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16