

Article

500.M1683
 INTERLOCKED SOCKET 2P+E IP44 16A 6h

Picture





Master data

Minimum order	1 NR
Net Weight	0.564 KG
EAN code	8001636120423
INTRASTAT code	85366990




TechData

Syntetical description	INTERLOCKED SOCKET
Commercial series	OMNIA Series
Protection degree	IP44
Flange	136X125MM_PAR
Rated current	16A
Poles	2P+E
Working frequency	50Hz
Working frequency	60Hz
Rated voltage	200-250V
Colour	BLUE
Hour position	6h

Approvals and Certifications



Standards and Laws

-  EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
-  EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636544687
Gross weight	3.702 KG
Volume	17812.5 CCM
Dimensions	150x475x250 (MM)

Annexed

Note:

Blank side with drilling point mark

