

**Article**

**513.1653**  
 SURF.MNT.SOCKET 2P+E IP44 16A 6h


**Picture****Master data**


Minimum order	10 NR
Net Weight	0.17 KG
EAN code	8001636231419
INTRASTAT code	85366990

**TechData**




Syntetical description	SURFACE MOUNTING SOCKET
Protection degree	IP44/IP54
Commercial series	OPTIMA-BASE Series
Cable outlet	M20X1,5
Rated current	16A
Poles	2P+E
Working frequency	50Hz
Working frequency	60Hz
Rated voltage	200-250V
Colour	BLUE
Hour position	6h

**Approvals and Certifications**

 I.M.Q. - ENEC 03  
 European Norms Electrical Certification

 CE  
 Declaration of conformity

**Standards and Laws**

-  EN 60309-1 (1999)  
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  EN 60309-2 (1999)  
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
-  EN 60309-1/A1 (2007)  
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)  
 [European Standard] Plugs, socket-outlets  
 and couplers for industrial purposes. Part 2:  
 Dimensional interchangeability requirements  
 for pin and contact-tube accessories of  
 harmonized configurations

**Packaging**

Description	Carton
Quantity	40
EAN code	8001636683522
Gross weight	8.4 KG
Volume	47151 CCM
Dimensions	390x390x310 (MM)
Description	Box
Quantity	10
EAN code	8001636683515
Gross weight	2.1 KG
Volume	9680 CCM
Dimensions	220x275x160 (MM)

**Annexed**



Technical drawing [DWG]




Technical drawing [PDF]



Technical drawing [STP]

**Note:**

- > Open threaded cable entry 
- > Threaded cap/cable sleeve included 