

SKINTOP® BS

SKINTOP® BS, polyamide cable gland with bending and anti-kink protection, to protect flexible cables, for moving machine parts



Variety of approval certifications



Temperature-resistant



Optimum strain relief



Mechanical resistance



Wide clamping range



Good chemical resistance

Benefits

Reliable bending and anti-kink protection

Cable protection

Functional reliability

To protect flexible cables

SKINTOP® BS

Application range

Cables connected to electrical appliances and machinery that are moved in normal use must be protected against excessive bending in accordance with VDE 0700-1.

Hand-held devices

Robotics industry

Light and sound applications

Moving machine parts

Norm references / approvals

UL file no. E79903

Design

PG connection thread

Note

Refer to SKINTOP® PG accessories for suitable accessories

Counter nut to be used: SKINTOP® GMP-GL

Version with reducing insert to seal smaller cable cross-sections, SKINTOP® BSR is available upon request

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Caution:	Refer to T21 for the installation dimensions and tightening torques
Colour delivered:	RAL 7001, silver grey RAL 9005, black/UV-resistant
Material:	Body: Polyamide Seal: CR
Protection rating:	IP 68 - 5 bar
Temperature range:	-20°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® BS**

Article number	Article designation / size	Clamping range ØF (mm)	SW mm	Total length C (mm)	Thread length, D (mm)
SKINTOP® BS silver grey					
53015600	PG 7	2.5 - 6.5	15	62	8
53015610	PG 9	3.5 - 8	19	73.5	8
53015620	PG 11	4 - 10	22	86	8
53015630	PG 13,5	6 - 12	24	98	9
53015640	PG 16	9 - 14	27	111.5	10
53015650	PG 21	13 - 18	33	129	11
SKINTOP® BS black					
53015800	PG 7	2.5 - 6.5	15	62	8
53015810	PG 9	3.5 - 8	19	73.5	8
53015820	PG 11	4 - 10	22	86	8
53015830	PG 13,5	6 - 12	24	98	9
53015840	PG 16	9 - 14	27	111.5	10
53015850	PG 21	13 - 18	33	129	11

Last Update (03.05.2017)

@2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16