

SKINTOP® ST-M SORTIMO® T-BOXX

SKINTOP® ST-M SORTIMO® T-BOXX, small packaging units, wide variety, wide, variable clamping ranges, easy to install, oil resistance

Info

Optimal order in the practical SORTIMO® T-BOXX

The brand for universal cable entry according to the principle: quickly fixed, centred and hermetically sealed



Variety of approval certifications



Temperature-resistant



Assembly time



Mechanical resistance



Wide clamping range



Good chemical resistance

Benefits

High oil resistance for maximum functional reliability

Wide, variable clamping ranges

Easy to install

Permanent vibration protection

Optimum strain relief

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® ST-M SORTIMO® T-BOXX

Application range

Control cabinet construction
Automation technology
Measurement, regulation and electrical applications
Air-conditioning technology

Product features

Optimal order in the practical SORTIMO® T-BOXX
Small packaging unit, wide variety
Light and robust, shock- and impact-resistant polypropylene case
Two robust locks - ideal for mounting use e.g. on building sites

Norm references / approvals

UL file no. E79903

Design

Metric connection thread according to DIN EN 60423
Basis for technical information DIN IEC 62444

Note

Standard packaging units are available for refills

Included in delivery

Delivery in SORTIMO® T-BOXX
Including counter nut SKINTOP® GMP-GL-M
Assembly instructions
50 pcs. SKINTOP® ST-M M12
art. no. 53111400
50 pcs. SKINTOP® ST-M M16
art. no. 53111410
40 pcs. SKINTOP® ST-M M20
art. no. 53111420
25 pcs. SKINTOP® ST-M M25
art. no. 53111430
9 pcs. SKINTOP® ST-M M32
art. no. 53111440

SKINTOP® ST-M SORTIMO® T-BOXX**Technical Data**

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Caution:	Refer to T21 for the installation dimensions and tightening torques
Colour delivered:	RAL 7035 light grey
Material:	Body: Polyamide Seal: CR
Tests:	GGVS: TÜ.EGG.020-95
Protection rating:	IP 68 - 5 bar IP 69
Temperature range:	dynamic: -20°C to +100°C static: -40°C to +100°C

Note

Other colours are available upon request.
Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINTOP® ST-M SORTIMO® T-BOXX

Article number	Article designation / size	Clamping range ØF (mm)
53110030	SKINTOP® ST-M SORTIMO® T-BOXX	-

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16