

SKINTOP® CLICK

SKINTOP® CLICK, plastic cable gland with time-saving latch system, simple, free assembly and vibration protection, no thread required

Info

The most innovative cable insertion system on the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - done. The result: fixed, centred, strain-relieved fitting and maximum protection rating in seconds.



Variety of approval certifications



UV-resistant



Temperature-resistant



Assembly time



Wide clamping range



Good chemical resistance

Benefits

Fewer parts, counter nut not needed
Save up to 70% more time with the innovative latch system
Simple, free assembly in any position
Vibration protection
No thread required

SKINTOP® CLICK

Application range

Automation technology
Solar applications
Control cabinet construction
Measurement, regulation and electrical applications
Air-conditioning technology

Norm references / approvals

UL file no. E79903

Included in delivery

Disassembly tool included in the scope of delivery

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Colour delivered:	RAL 7001 silver grey RAL 7035 light grey RAL 9005 black/UV-resistant
Material:	Body: Special polyamide Seal: Special elastomer
Protection rating:	IP 68 - 4 bar (M12) IP 68 - 5 bar (M16 - M25) IP 68 - 1 bar (M32)
Temperature range:	dynamic: -20°C to +100°C static: -40°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® CLICK**

Article number	Article designation / size	Clamping range ØF (mm)	M (hole in mm)	SW1/SW2 mm	Total length C (mm)	Thread length, D (mm)	Wall thickness, S (mm)
SKINTOP® CLICK light grey							
53112692	CLICK 12	4.5 - 7	12.3 (-0.2)	15 / 18	40	8	1 - 4
53112686	CLICK 16	5 - 9	16.3 (-0.2)	19 / 22	42	8	1 - 4
53112687	CLICK 20	7 - 13	20.3 (-0.2)	25 / 27	45.5	8	1 - 4
53112688	CLICK 25	9 - 17	25.3 (-0.2)	30 / 34	48.5	8	1 - 4
53112694	CLICK 32	11 - 21	32.3 (-0.2)	36 / 40	55	8	1 - 4
SKINTOP® CLICK silver grey							
53112921	CLICK 12	4.5 - 7	12.3 (-0.2)	15 / 18	40	8	1 - 4
53112876	CLICK 16	5 - 9	16.3 (-0.2)	19 / 22	42	8	1 - 4
53112877	CLICK 20	7 - 13	20.3 (-0.2)	25 / 27	45.5	8	1 - 4
53112878	CLICK 25	9 - 17	25.3 (-0.2)	30 / 34	48.5	8	1 - 4
53112922	CLICK 32	11 - 21	32.3 (-0.2)	36 / 40	55	8	1 - 4
SKINTOP® CLICK black							
53112923	CLICK 12	4.5 - 7	12.3 (-0.2)	15 / 18	40	8	1 - 4
53112882	CLICK 16	5 - 9	16.3 (-0.2)	19 / 22	42	8	1 - 4
53112883	CLICK 20	7 - 13	20.3 (-0.2)	25 / 27	45.5	8	1 - 4
53112884	CLICK 25	9 - 17	25.3 (-0.2)	30 / 34	48.5	8	1 - 4
53112924	CLICK 32	11 - 21	32.3 (-0.2)	36 / 40	55	8	1 - 4

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SKINTOP® CLICK

