

SKINTOP® CLICK BS

SKINTOP® CLICK BS, bending protection with innovative latch system to protect flexible cables, no thread required, no counter nut

Info

The most innovative cable insertion system on the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - done. The result: fixed, centred, strain-relieved fitting and maximum protection rating in seconds.



Variety of approval certifications



Acid-resistant



Space requirement



Assembly time



Mechanical resistance



Heat-resistant



Good chemical resistance

Last Update (02.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® CLICK BS

Benefits

Reliable bending protection for cable conservation and functional reliability
Save up to 70% more time with the innovative latch system
No thread required
To protect flexible cables
Fewer parts, counter nut not needed

Application range

Cables connected to electrical appliances and machinery that are moved in normal use must be protected against excessive bending in accordance with VDE 0700-1.
Robotics industry
Moving machine parts
Apparatus construction
Light and sound applications

Norm references / approvals

UL file no. E79903

Included in delivery

Disassembly tool included in the scope of delivery

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Colour delivered:	RAL 7001 silver grey RAL 7035 light grey RAL 9005 black/UV-resistant
Material:	Body: Special polyamide Seal: Special elastomer
Protection rating:	IP 68 - 4 bar (M12) IP 68 - 5 bar (M16 - M25) IP 68 - 1 bar (M32)
Temperature range:	-20°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



SKINTOP® CLICK BS

Article number	Article designation / size	Clamping range ØF (mm)	M (hole in mm)	SW1/SW2 mm	Total length C (mm)	Thread length, D (mm)	Wall thickness, S (mm)
SKINTOP® CLICK BS light grey							
53112932	CLICK BS 12	4.5 - 7	12.3 (-0.2)	18 / 15	74	8	1 - 4
53112888	CLICK BS 16	5 - 9	16.3 (-0.2)	22 / 19	94	8	1 - 4
53112889	CLICK BS 20	7 - 13	20.3 (-0.2)	27 / 25	108	8	1 - 4
53112890	CLICK BS 25	9 - 17	25.3 (-0.2)	32 / 30	127	8	1 - 4
53112933	CLICK BS 32	11 - 21	32.3 (-0.2)	40 / 36	155	8	1 - 4
SKINTOP® CLICK BS silver grey							
53112934	CLICK BS 12	4.5 - 7	12.3 (-0.2)	18 / 15	74	8	1 - 4
53112906	CLICK BS 16	5 - 9	16.3 (-0.2)	22 / 25	94	8	1 - 4
53112907	CLICK BS 20	7 - 13	20.3 (-0.2)	27 / 25	108	8	1 - 4
53112908	CLICK BS 25	9 - 17	25.3 (-0.2)	32 / 30	127	8	1 - 4
53112935	CLICK BS 32	11 - 21	32.3 (-0.2)	40 / 36	155	8	1 - 4
SKINTOP® CLICK BS black							
53112936	CLICK BS 12	4.5 - 7	12.3 (-0.2)	18 / 15	74	8	1 - 4
53112909	CLICK BS 16	5 - 9	16.3 (-0.2)	22 / 19	94	8	1 - 4
53112911	CLICK BS 20	7 - 13	20.3 (-0.2)	27 / 25	108	8	1 - 4
53112912	CLICK BS 25	9 - 17	25.3 (-0.2)	32 / 30	127	8	1 - 4
53112937	CLICK BS 32	11 - 21	32.3 (-0.2)	40 / 36	155	8	1 - 4

Last Update (02.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

SKINTOP® CLICK BS

