

SKINTOP® GMP-HF-M

SKINTOP® GMP-HF-M, extremely flame-retardant, halogen-free counter nut, self-extinguishing, no drop formation, for public buildings

Info

Cable entry for railway applications



Variety of approval certifications



Temperature-resistant



Assembly time



Halogen-free

Benefits

Halogen-free

Extremely flame-retardant according to UL 94 V0

Self-extinguishing, drop formation

Application range

For locking SKINTOP® cable glands in boreholes without thread.

Airports

Tunnel constructions

Underground railways

Public buildings

SKINTOP® GMP-HF-M

Design

Metric connection thread according to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

Designed for use with SKINTOP® ST-HF-M

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable gland
Colour delivered:	RAL 7035 light grey
Material:	Polyamide UL 94V-0 - halogen-free
Temperature range:	static: -40 °C to +100 °C dynamic: -20 °C to +100 °C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® GMP-HF-M**

Article number	Article designation / size	SW mm
SKINTOP® GMP-HF-M		
53119200	M 12 x 1,5	17
53119210	M 16 x 1,5	22
53119220	M 20 x 1,5	27
53119230	M 25 x 1,5	34
53119240	M 32 x 1,5	41
53119250	M 40 x 1,5	50
53119260	M 50 x 1,5	60
53119270	M 63 x 1,5	75

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16