

SKINTOP® DIX-AUTOMATION

SKINTOP® DIX-AUTOMATION, NBR seals with optimal seal when using AS-I bus cables, strain relief



UV-resistant



Temperature-resistant



Reliability



Assembly time



Automation & fältinstallation

Benefits

Optimal seal when using AS-I bus cables
Strain relief

Application range

These seals can be used instead of our standard seals in the SKINTOP® cable glands.
Control cabinets
Control panels
Office applications

Note

IP 68 can be achieved if the hole is optimally occupied, i.e. when using standard AS-I cables

Product Make-up

Precise cut for AS-I bus cables

Last Update (29.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® DIX-AUTOMATION

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: Plug for cable screw gland
Colour delivered:	Black, RAL 9005
Material:	NBR
Protection rating:	IP 54
Temperature range:	-40°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINTOP® DIX-AUTOMATION

Article number	Article designation / size
SKINTOP® DIX ASI	
53611000	DIX ASI 11

Last Update (29.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16