

SKINTOP® SDV-M ATEX

SKINTOP® SDV-M ATEX dust protection



Reliability



Assembly time

Benefits

Permanent and secure sealing for areas with risks of explosion
Easy to assemble
High protection rating

Application range

SKINTOP® SDV-M is used together with SKINTOP® MS-M ATEX, MS-M ATEX BRUSH or SKINTOP® K-M ATEX plus (blue).
Equipment group II / category 2G+1D

Note

Outside areas with a risk of explosion, also suitable for use with SKINTOP® ST-M and SKINTOP® MS-M

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: Screw plug
Caution:	Refer to the package insert for the installation dimensions and tightening torques
Material:	CR
Protection rating:	IP 68 - 10 bar
Temperature range:	-30°C to +70°C short-term: up to +90°C

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® SDV-M ATEX

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® SDV-M ATEX**

Article number	Article designation / size	Head height (mm) SKINTOP®
SKINTOP® SDV-M ATEX		
54113002	M 12 ATEX	SDV-M ATEX 3
54113012	M 16 ATEX	SDV-M ATEX 3
54113022	M 20 ATEX	SDV-M ATEX 3.5
54113032	M 25 ATEX	SDV-M ATEX 3.5
54113042	M 32 ATEX	SDV-M ATEX 4
54113052	M 40 ATEX	SDV-M ATEX 4
54113062	M 50 ATEX	SDV-M ATEX 4.5
54113072	M 63 ATEX	SDV-M ATEX 4.5

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16