

SKINTOP® SDVR-M ATEX

SKINTOP® SDV-M ATEX dust protection



Reliability



Assembly time

Benefits

For the benefits, refer to SKINTOP® SDV-M ATEX

Application range

SKINTOP® SDVR-M is used together with SKINTOP® MSR-M ATEX or SKINTOP® KR-M ATEX plus (blue).
Equipment group II / category 2G+1D

Note

Outside areas with a risk of explosion, also suitable for use with SKINTOP® STR-M and SKINTOP® MSR-M

Technical Data

Classification:

ETIM 5.0 Class-ID: EC000032

ETIM 5.0 Class-Description: Screw plug

Caution:

Refer to the package insert for the installation dimensions and tightening torques

Material:

CR

Protection rating:

IP 68 - 10 bar

Temperature range:

-30°C to +70°C

short-term: up to +90°C

Last Update (04.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® SDVR-M ATEX

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



SKINTOP® SDVR-M ATEX

Article number	Article designation / size	Head height (mm) SKINTOP®
SKINTOP® SDVR-M ATEX		
54113013	M 16 ATEX	SDVR-M ATEX 4
54113023	M 20 ATEX	SDVR-M ATEX 5
54113033	M 25 ATEX	SDVR-M ATEX 5
54113043	M 32 ATEX	SDVR-M ATEX 5.5

Last Update (04.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16