

**Article**


**590.EM4015**  
SWITCH DISCONNECTOR 40A 3P+N IP65





**Picture****Master data**

Minimum order	1 NR
Net Weight	0.384 KG
EAN code	8001636265247
INTRASTAT code	85365080

**TechData**

Syntetical description	SWITCH DISCONNECTOR
Protection degree	IP65
Commercial series	ISOLATORS Series
Type	EMERGENCY
Colour	YELLOW/RED
Rated current	40A
Poles	3P+N
Switch size	Y1
Dimension	105x150x82mm





**Approvals and Certifications****Standards and Laws**

-  EN 60947-3 (2006)  
[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
-  EN 60947-1 (2007)  
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
-  EN 60947-1/A1 (2011)  
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
-  EN 60947-3/A1 (2011)  
[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units








**Packaging**

Description	Carton
Quantity	12
EAN code	8001636711515
Gross weight	5.82 KG
Volume	36800 CCM
Dimensions	320x460x250 (MM)
Description	Box
Quantity	1
EAN code	8001636711508
Gross weight	0.485 KG
Volume	2121.168 CCM
Dimensions	107x168x118 (MM)

**Annexed**

-  Instruction manual
-  Technical drawing [DWG]
-  Technical drawing [PDF]
-  Technical drawing [STP]

**Note:**

-  Handle padlockable in OFF only (3 padlocks) 
-  Equipped with door interlock 
-  With late break and early make neutral pole 
-  Break-through cable entries 