

## Product information M12 Single Ended Cordsets - Standard Types, A and U coding - RKWT 8-282/5 M

Name	M19 Cinnia Endad Covdocto - Chandard Turco - A and II anding
Name	M12 Single Ended Cordsets - Standard Types, A and U coding
	Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, 8 poles, PUR jacket, 5 meters
Delivery informations	
Availability	available
Product description	
Туре	RKWT 8-282/5 M
Order No.	64547
Description	Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, 8 poles, PUR jacket, 5 meters
Number of contacts	8
Color of housing	black translucent
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	angled
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	
Environmental conditions	
Environmental temperature	-25 °C 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU
Contact bearer material	TPU
Contact material	CuSn
Contact material - Surface refinement	pre-nickeled and gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	TANK
Contact resistance	$\leq 5 \text{ m}\Omega$
Rated current In	2 A at 40°C, UL and notice derating
Nominal voltage	30 V
	36 V
Rated voltage	
Test voltage	1.5 kV eff./60 s
Insulation resistance	>1 GΩ
Approvals	THE STATE OF THE S
Approvals	UL