


EPIC® SIGNAL M23 inserts 8+1-pin

Inserts for M23 circular connectors

EPIC® SIGNAL M23 inserts 8+1-pin for M23 circular connector series



Variety of approval certifications



Robust



Assembly time



Mechanical resistance



Good chemical resistance



Wind Energy



Industrial machinery and plant engineering

Benefits

Universal further processing of the M23 inserts through different packaging units. Fully equipped with suitable soldering contacts or unequipped for individual fitting with soldering or crimping contacts

Application range

Plant construction

Measurement, control and regulation technology

Apparatus construction

Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® SIGNAL M23 inserts 8+1-pin

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000438 ETIM 5.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V):	according to IEC 61984: 150 V
Rated impulse voltage:	2.5 kV
Rated current in A:	20 A (2 mm contact) 7 A (1 mm contacts)
Pollution degree:	3
Contact resistance:	< 4 mOhm
Contacts:	Gold-plated brass
Number of contacts:	8 + 1
Cable connection:	Crimp termination: 0.14 - 1.0 mm ² (1.0 - 2.5 mm ² for 2mm contact) Solder termination: up to 1.0 mm ² (up to 2.5 mm ² for 2mm contact)
Plug cycles:	100
VDE-tested:	Certified production control: VDE reg. no. C24 (according to EN 61984, SELV according to DIN VDE 0100-410 has to be guaranteed) UL file number: E249137
Temperature range:	-25°C to +125°C

Note

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-part and one E-part.
P-component = left turning, E-component = right turning
Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® SIGNAL M23 inserts 8+1-pin**

Article number	Article description	Inserts	Pin configuration
8+1-pin inserts, P-part = rotation to the left (anticlockwise)			
73002736	P-part	without contacts	8+1
73002737	P-part	without contacts	8+1
73002738	P-part	+ male contacts, solder	9
73002739	P-part	+ male contacts, solder	9
73002740	P-part	+ female contacts, solder	9
73002741	P-part	+ female contacts, solder	9
8+1-pin inserts, E-part = rotation to the right (clockwise)			
73002742	E-part	without contacts	8+1
73002743	E-part	without contacts	8+1
73002744	E-part	+ male contacts, solder	9
73002745	E-part	+ male contacts, solder	9
73002746	E-part	+ female contacts, solder	9
73002747	E-part	+ female contacts, solder	9

Last Update (09.05.2017)



©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® SIGNAL M23 inserts 8+1-pin



Last Update (09.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16