


Product information

0906 UTP 104

Name	0906 UTP 104
	
	T-connector incl. mounting hole, M12 female with two M12 male connectors, 5 poles, especially suitable to connect decentral 24 V power supply (Power module) with (LioN-Link-) I/O modules
Delivery informations	
Availability	available
Product description	
Type	0906 UTP 104
Order No.	98611
Description	T-connector incl. mounting hole, M12 female with two M12 male connectors, 5 poles, especially suitable to connect decentral 24 V power supply (Power module) with (LioN-Link-) I/O modules
Number of contacts	5
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance
Classification	
Belden brand	Lumberg-Automation
Environmental conditions	
Environmental temperature	-25 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	TPU, self-extinguishing
Contact material	CuZn
Contact material - Surface refinement	pre-nickeled and 0.3 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I _n	4 A at 40 °C
Nominal voltage	60 V
Rated voltage	63 V
Test voltage	1.5 kV eff./60 s
Insulation resistance	> 1 GΩ

Picture
Drawing

