

UNITRONIC® BUS CAN BURIAL

For CAN based communication acc. ISO 11898, direct burial, outdoor applications. Rugged, UV-resistant and weatherproof, temperature range from -40°C bis +80°C

Info

Suitable for direct burial



UV-resistant



Robust



Mechanical resistance



Corrosion-resistant



Solar Energy



Kompletterande automationskomponenter från Lapp



Suitable for outdoor use

Benefits

Suitable for CAN communication according to ISO 11898

Double-sheathed version, extremely tough, for installation without corrugated tubing

Rugged, UV-resistant and weatherproof

Diameter of inner sheath suitable for common connectors

Application range

Useable for CAN based communication systems like CANopen

Suitable for direct burial

For outdoor applications

For fixed installation or applications with occasional movements

Last Update (26.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® BUS CAN BURIAL

Product Make-up

Copper stranded 7x0,32
Core insulation made of polyethylene (PE)
Colour-coded in accordance with DIN 47100
Overall screening of braided tinned-copper strands
Sheath 1: PVC violet, Outer diameter 7,1 mm
Sheath 2: PE black, Outer diameter ca. 9 mm

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable
Mutual capacitance:	(1 kHz): max. 40 nF/km
Peak operating voltage:	300 V (not for power applications)
Conductor resistance:	(Loop): max. 74 Ohm /km
Minimum bending radius:	Flexible use: 8 x Outer Diameter Fixed Installation: 4 x Outer Diameter
Test voltage:	Core/core: 1500 V rms
Characteristic impedance:	120 ohm
Temperature range:	Fixed installation: -40°C to +80°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

UNITRONIC® BUS CAN BURIAL

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index [kg/km]	Weight [kg/km]
2170500	4 x 1 x 0.5	9	41.8	91

Last Update (26.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16