

CHARGE M3 ---/T1C S

Charge charging cable with type 1 connector, length 5m as component of a charging station

Info

For charging stations



UV-resistant



Robust



Oil-resistant



Mechanical resistance



e-Mobility



Suitable for outdoor use



Cold-resistant

Benefits

new two-chamber system for environmental protection of moving parts to the connection part

Resistant to oil, dust and water

Special cable design for a long service life

Flexible at low temperatures

Withstands high mechanical stress, in particular abrasion and sliding demands

Last Update (07.05.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

CHARGE M3 ---/T1C S

Application range

For installation in charging stations

Product Make-up

Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm²+1x0.5 mm²

Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm²+1x0,5mm²

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002839

ETIM 5.0 Class-Description: Accessories for battery/charger

Certifications:

according to VDE-AR-E2283-5

according to EN 61851-1

Temperature range:

Flexing: -30 °C to +50 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Further colour combinations and lengths on request

CHARGE M3 ---/T1CS

Article number	Version	Effective length (mm)	Copper index kg/1.000 pieces	Weight (kg/1000 pieces)
Cut off clean, charging cable, vehicle connector type 1 (Total length: effective length +1m straight)				
74880127	Charging: 1 phase 20A	5000	479	1240
74880128	Charging: 1 phase 20A	7000	633	1540
74880130	Charging: 1 phase 32A	5000	1057	2100
74880131	Charging: 1 phase 32A	7000	1413	2740