

CONFIX WST

Split corrugated conduits



Individual lengths are possible!

Product description

The CONFiX WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. KVT-W90, a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of split grommets offered (see KT grommets on pages 44 - 46).

The length of the CONFiX WST split corrugated conduit can be customized to your application. All conduits are available by the meter (0.5 m steps).

Advantages & benefits

- Containing pre-terminated cables, warranty of cable remains
- Retrofitting and maintenance carried out easily and quickly

Type	Order No.	Internal diameter	External diameter	Compatible grommets	Dimensions	Ring length*
CONFIX WST NW 10	31200	8.7 mm	13.6 mm	KT 13	NW 10	50 m*
CONFIX WST NW 14	31210	12.5 mm	18.5 mm	KT 18	NW 14	50 m*
CONFIX WST NW 20	31220	19.5 mm	25.5 mm	KT 25	NW 20	50 m*
CONFIX WST NW 23	31230	24.2 mm	31 mm	KT 30	NW 23	50 m*
CONFIX WST NW 29	31235	27.3 mm	35.5 mm	KTMB-P	NW 29	25 m*
CONFIX WST NW 37	31240	31 mm	41.4 mm	KTMB-P	NW 37	25 m*
CONFIX WST NW 45	31250	42.7 mm	54 mm	KTMB-Q	NW 45	25 m*
CONFIX WST NW 70	31260	66.5 mm	79.8 mm	KTMB-S	NW 70	10 m*

*All conduits are also available by the metre (0.5 m steps).

Specifications

Material	Polypropylene, black
Flame class	UL94-HB
Temperature	- 40°C to + 105°C
Properties	UV resistant

Compatible with

CONFIX SH Conduit clip	161
Cable entry systems for pre-terminated cables	8 - 69
Cable entry systems for standard cables	72 - 94