

ETHERLINE® LAN FLEX

Data cable for patchcable applications

The LAN cable has good flexibility and can be installed easily in restricted spaces. The cable is suitable for connection in control cabinets.

Info

Only for patch cable applications (max. 60 m)



Interference signals



Halogen-free

Benefits

For directly connecting two electric components
Easy to assemble

Application range

Indoor applications
LAN connections
Control cabinet wiring

Product features

Good flexibility - easy installation with tight space requirements
Flame retardant acc. to IEC 60332-1-2
2170139: flame retardant acc. to IEC 60332-1-2 and IEC 60332-3-24

Product Make-up

F/UTP: foil screening as overall screening
SF/UTP: braid of tinned copper wire and plastic laminated aluminum foil as overall screening
S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
outer sheath either as PVC or LSZH (color grey RAL 7035)

Last Update (08.02.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ETHERLINE® LAN FLEX**Technical Data**

| | |
|-------------------------|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000830 ETIM 6.0 Class-Description: Data cable |
| Minimum bending radius: | during installation: 8 x outer diameter Fixed installation: 4 x outer diameter |
| Temperature range: | Operating temperature: -20 °C to +60 °C During installation: 0 °C to +50 °C |

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil 100 m; Drum (500; 1000) m

Detailed data sheets are available upon request. Please specify the type/dimensions of the required cable.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



ETHERLINE® LAN FLEX

| Article number | Article designation | Number of pairs and AWG per conductor | Outer diameter [mm] | Copper index (kg/km) | Weight (kg/km) |
|-----------------------|------------------------|---------------------------------------|---------------------|----------------------|----------------|
| PVC versions | | | | | |
| 2170127 | 200 F/UTP Cat.5e | 4 x 2 x AWG26/7 | 5.6 | 13 | 28 |
| 2170129 | 200 SF/UTP Cat.5e | 4 x 2 x AWG26/7 | 6 | 22 | 36 |
| 2170144 | 600 S/FTP CAT7 Y | 4 x 2 x AWG26/7 | 6.5 | 22 | 39 |
| Halogen-free versions | | | | | |
| 2170172 | 200 F/UTP Cat.5e LSZH | 4 x 2 x AWG26/7 | 5.6 | 13 | 28 |
| 2170139 | 200 SF/UTP Cat.5e LSZH | 4 x 2 x AWG26/7 | 6 | 22 | 36 |
| 2170142 | 600 S/FTP CAT7 LSZH | 4 x 2 x AWG26/7 | 6.2 | 21 | 40 |

Last Update (08.02.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

ETHERLINE® LAN FLEX



Last Update (08.02.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16