

EVCP2 Controller Mode 3/ Typ 2

Integrated power supply unit 230V/12V with power supply in case of power failure, Control of charging contactor and connector lock and LED

Info

For optimal control of the type 2 socket outlets



Benefits

- For safe and continuous charging
- Power reserve for plug release in case of power failure
- Additional 12V outputs for peripherals

Product features

- Integrated power supply unit 230V/12V with power supply in case of power failure
- Adjustable charging current of 6A-80A by means of rotary switch
- For each type 2 socket outlet EVCP2 one controller is necessary
- Possibility to control the RGB LED lighting
- Control of charging contactor and connector lock

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002839 ETIM 5.0 Class-Description: Accessories for battery/charger
Nominal voltage:	95 ... 265 V AC
Protection rating:	IP 30
Temperature range:	Operation: -20 °C to +70 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

EVCP2 Controller Mode 3/ Typ 2

Article number	Article designation
EVCP2 Controller Mode 3 / Type 2	
74880215	Standard + query via RS485
74880216	Vehicle connector firmly connected to EVSE, suitable for type 1 and type 2, query via RS485
74880217	Standard + query via RS485 + hinged lid locking + limit switch
74880218	Standard + query via RS485 + analog input
74880219	Vehicle connector firmly connected to EVSE, suitable for Type 1 and Type 2, query via RS485 + analog input
74880220	Standard + query via RS485 + hinged lid locking + limit switch + analog input
Software for EVCP2 controllers including manual	
74880221	To adjust and for query via RS232 / RS485
Connecting cable for plug and hinged lid locking	
74880222	Acutator coupler with single cores 3x0.5, length 1000mm