

HITRONIC® TORSION

Breakout cable specially designed to withstand high torsional stresses; PUR outer sheath

Fibre optical cables for wind applications with defined movement, torsion, available with 2,4,8 or 12 sub-cable elements with single-mode or multimode fibres

Info

Torsion-resistant and very flexible



UV-resistant



Torsion-resistant



Optimum strain relief



Low weight



Mechanical resistance



Halogen-free



Wind Energy



Kompletterande automationskomponenter från Lapp

Benefits

Designed to withstand high torsion in the windmill drip loop

Suitable for field assembly

Easy to install due to the compact design, high flexibility, robust sheath and small bending radii

Zero electromagnetic interference as the cable contains no metal (totally dielectric)

Last Update (25.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

HITRONIC® TORSION

Application range

For fixed and flexible installations, as well as for applications with torsional movements (e.g. machinery, wind turbines)
Industrial environments
In vertical installations
As a link between moving parts
For indoor and outdoor use

Product features

Based on military norm MIL-C-85045
Torsion-resistant and very flexible
Outer sheath flame-retardant and halogen-free
Mechanically robust

Product Make-up

2.5 mm tight-buffered sub-cable with
LSZH sheath
Aramid yarns as strain relief
Central element
PUR outer sheath
Colour: black (RAL 9005)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000034 ETIM 5.0 Class-Description: Fibre optic cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000034 ETIM 6.0 Class-Description: Fibre optic cable
Dimensions:	sub-cable: 2.5mm Cable: see table
Core identification code:	Details see datasheet
Fibre type:	GOF - Glass Optical Fibre
Standard designation:	A/J-V(ZN)H11Y
Optical values:	see data sheet
Optical fibre type:	Core material: glass Cladding material: glass
Permissible bending radius:	Static: $\geq 15 \times$ outer diameter Dynamic: $\geq 20 \times$ outer diameter
Temperature range:	Fixed installation: -40°C to $+70^{\circ}\text{C}$ Occasional flexing: -30°C to $+70^{\circ}\text{C}$

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.
Available on request with Multimode OM4 fibres.

HITRONIC® TORSION

Article number	Article designation	Fibre type	Number of fibres	Outer diameter [mm]	Weight (kg/km)
Multimode G 50 OM3					
26310302	HITRONIC® TORSION 2G 50/125 OM3	50/125 OM3	2	8.4	54
26310304	HITRONIC® TORSION 4G 50/125 OM3	50/125 OM3	4	8.4	54
26310308	HITRONIC® TORSION 8G 50/125 OM3	50/125 OM3	8	11.6	95
26310312	HITRONIC® TORSION 12G 50/125 OM3	50/125 OM3	12	14.7	122
Multimode G 50 OM2					
26310202	HITRONIC® TORSION 2G 50/125 OM2	50/125 OM2	2	8.4	54
26310204	HITRONIC® TORSION 4G 50/125 OM2	50/125 OM2	4	8.4	54
26310208	HITRONIC® TORSION 8G 50/125 OM2	50/125 OM2	8	11.6	95
26310212	HITRONIC® TORSION 12G 50/125 OM2	50/125 OM2	12	14.7	122
Multimode G 62.5 OM1					
26310102	HITRONIC® TORSION 2G 62.5/125 OM1	62.5/125 OM1	2	8.4	54
26310104	HITRONIC® TORSION 4G 62.5/125 OM1	62.5/125 OM1	4	8.4	54
26310108	HITRONIC® TORSION 8G 62.5/125 OM1	62.5/125 OM1	8	11.6	95
26310112	HITRONIC® TORSION 12G 62.5/125 OM1	62.5/125 OM1	12	14.7	122
Single-mode E 9 OS2					
26310902	HITRONIC® TORSION 2E 9/125 OS2	9/125 OS2	2	8.4	54
26310904	HITRONIC® TORSION 4E 9/125 OS2	9/125 OS2	4	8.4	54
26310908	HITRONIC® TORSION 8E 9/125 OS2	9/125 OS2	8	11.6	95
26310912	HITRONIC® TORSION 12E 9/125 OS2	9/125 OS2	12	14.7	122

Last Update (25.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16