



KEL-DPZ 16

Cable entry plates



Also available with threaded bushings.



Membrane on front

Product description

2.1

KEL-DPZ 16 entry plates are designed to route and seal up to 34 cables without connectors or fibre optics (from 1.5 mm to 16.2 mm in diameter) in limited space.

The size KEL-DPZ 16 matches exactly the cut-out dimensions of 16-pin standard industrial connectors.

The assembly of the KEL-DPZ 16 with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ 16 provides strain relief and protection up to IP66. ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Advantages & benefits

- Fast and easy assembly
- High cable density
- Dual sealing acc. to IP65/IP66
- Automatic sealing and strain relief for the cable
- Hygienic design

Specifications

Material	Frame: Polyamide (PA) Sealing plate: Elastomer
Colour	■ grey (similar RAL 7035)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP65/IP66 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	36 × 86 mm / page 218 - 219
Plate depth	14 mm

Accessories

ST-B Plugs	85
KEL-EMC-PF Cable collectors	139
FP Flanged plates	178 - 183

XX

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ 16 11	43815	11× 7.5 - 12 mm	10
	KEL-DPZ 16 14	43816	5× 3.2 - 6.5 mm 5× 5 - 10.2 mm 4× 9 - 16.2 mm	10
	KEL-DPZ 16 20	43817	11× 3.2 - 6.5 mm 5× 5 - 10.2 mm 4× 7.5 - 12 mm	10
	KEL-DPZ 16 25	43818	16× 3.2 - 6.5 mm 6× 5 - 10.2 mm 3× 7.5 - 12 mm	10
	KEL-DPZ 16 34	43819	34× 3.2 - 6.5 mm	10