




**Product information**

**0935 253 101 - 0935 253 101/2 M  
10961**

|                                       |  |   |
|---------------------------------------|--|---|
| Name                                  |  | 0935 253 101  |
|                                       |  |    |
|                                       |  | CAN/DeviceNet Thin Cable molded on both sides with 7/8" male connector and M12 female connector, 5 poles, 2 meter, PUR jacket, halogen free, black. |
| Delivery informations                 |  |   |
| Availability                          |  | available   |
| Product description                   |  |   |
| Type                                  |  | 0935 253 101/2 M  |
| Order No.                             |  | 10961   |
| Description                           |  | CAN/DeviceNet Thin Cable molded on both sides with 7/8" male connector and M12 female connector, 5 poles, 2 meter, PUR jacket, halogen free, black. |
| Note                                  |  | The application of these products in harsh environments should always be checked before use.  |
| Color of housing                      |  | black   |
| Product characteristics               |  | Oil resistance, EMC resistance, Vibration resistance  |
| Classification                        |  |   |
| Belden class                          |  | Data cables   |
| Belden brand                          |  | Lumberg-Automation  |
| Approvals                             |  |   |
| Approvals                             |  | UL  |
| Cable                                 |  |   |
| Cable length                          |  | 2 m   |
| Cable number                          |  | 253   |
| Cable description                     |  | Bus cable: DeviceNet-CANopen®   |
| Color of jacket                       |  | black   |
| Material of outer jacket              |  | PUR   |
| Without halogens as in EN 50267-2-3   |  | ✓   |
| shielded                              |  | ✓   |
| welding spark proof                   |  | ✗   |
| Outer diameter of the cable           |  | 6.7 mm  |
| Number of conductors                  |  | 4   |
| Cable design                          |  | 1 x 2 x 0.25 mm <sup>2</sup> (AWG 24); 1 x 2 x 0.34 mm <sup>2</sup> (AWG 22)  |
| Flame resistant according to standard |  | IEC 60332-1-2, UL VW-1, CSA FT-1  |