




Product information

**0935 253 302 - 0935 253 302/3 M
10977**

| | | |
|---------------------------------------|--|--|
| Name | | 0935 253 302 |
| | |  |
| | | CAN/DeviceNet Thin Cable molded on one side with 7/8" male connector, 5 poles, 3 meter, PUR jacket, halogen free, black. |
| Delivery informations | | |
| Availability | | available |
| Product description | | |
| Type | | 0935 253 302/3 M |
| Order No. | | 10977 |
| Description | | CAN/DeviceNet Thin Cable molded on one side with 7/8" male connector, 5 poles, 3 meter, PUR jacket, halogen free, black. |
| Note | | The application of these products in harsh environments should always be checked before use. |
| Color of housing | | orange |
| Product characteristics | | Oil resistance, EMC resistance, Vibration resistance |
| Classification | | |
| Belden class | | Data cables |
| Belden brand | | Lumberg-Automation |
| Cable | | |
| Cable length | | 3 m |
| Cable number | | 253 |
| Cable description | | Bus cable: DeviceNet-CANopen® |
| Color of jacket | | black |
| Material of outer jacket | | PUR |
| Without halogens as in EN 50267-2-3 | | ✓ |
| shielded | | ✓ |
| welding spark proof | | ✗ |
| Outer diameter of the cable | | 6.7 mm |
| Number of conductors | | 4 |
| Cable design | | 1 x 2 x 0.25 mm ² (AWG 24); 1 x 2 x 0.34 mm ² (AWG 22) |
| Flame resistant according to standard | | IEC 60332-1-2, UL VW-1, CSA FT-1 |