




Product information RKM - RKM 4-07/5 M 11285

Name	RKM
	T T
	I I
	Cordsets, single-ended, for actuator/sensors and distribution boxes, M8 female connector, straight, with snap-in joint and molded cable, 4 poles, PVC jacket
	orange, 5 meters.
Delivery informations	
Availability	available
Product description	DVA A CYC N
Type	RKM 4-07/5 M
Order No.	11285
Description	Cordsets, single-ended, for actuator/sensors and distribution boxes, M8 female connector, straight, with snap-in joint and molded cable, 4 poles, PVC jacke orange, 5 meters.
Note	The application of these products in harsh environments should always be checked before use.
Number of contacts	4
Color of housing	black translucent
Classification	Didok transiticent
Belden brand	Lumberg-Automation
Mechanical data	Lumbery-Automation
Type of plug-in contact	Female connector
Design of housing	straight
Thread	M8
Design of electrical connection	connector M8
LED display present	X X
Environmental conditions	
Environmental temperature	-40 °C 90 °C
Degree of protection (IP), mounted	IP65
Pollution degree	3
Materials	
Housing material / Molded body	TPU
Contact bearer material	PA/TPU
Contact material	CuZn
Contact material - Surface refinement	pre-nickeled and 0.8 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Electrical data	ouzi, monor parou
Contact resistance	≤5 mΩ
Rated current In	4 A at 40°C
Nominal voltage	30 V
Rated voltage	36 V
Test voltage	0.8 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	/ 1 U3£
Approvals	UL
Cable	^{vL}
Cable length	5 m
Cable number	07
Cable description	Sensor connecting cable
	as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Color of jacket	orange
Material of outer jacket	PVC
Without halogens as in EN 50267-2-3	×
shielded	×
welding spark proof	×
Outer diameter of the cable	5.0 mm
Number of conductors	4
Cable design	4 x 0.25 mm ²
Conductor design	32 x 0.10 mm
Flame resistant according to standard	none
Picture	

Drawing





4-polig 4 poles



1 = braun / brown 2 = weiß / white 3 = blau / blue 4 = schwarz / black

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.