




Product information
Field Attachable M12 Connectors -
Standard Type - RSCW3/9
11600

Name	
Name	Field Attachable M12 Connectors - Standard Type
	
	Field attachable connector, M12 male connector, right angled version, with threaded joint, assembling with screw terminals
Delivery informations	
Availability	available
Product description	
Type	RSCW 3/9
Order No.	11600
Description	Field attachable connector, M12 male connector, right angled version, with threaded joint, assembling with screw terminals
Number of contacts	3
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Male connector
Design of housing	angled
LED display present	✘
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.75 mm ²
Screw joint for cable for external cable diameter	4.0 mm ... 8.0 mm
Screwed cable gland, connecting thread	SW 19
Environmental conditions	
Environmental temperature	-25 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-coppered, CuSnZn
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I _n	4 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage (Value)	250 V
Test voltage	2.0 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.