




Product information

**0975 254 102 - 0975 254 102/1 M
12503**

| | | |
|---------------------------------------|--|--|
| Name | | 0975 254 102 |
| | |  |
| | | Profibus signal cable, molded on one side with M12 male connector, 5 poles, B coding, 1 meter, PUR jacket, halogen free, shielded, violet. |
| Delivery informations | | |
| Availability | | available |
| Product description | | |
| Type | | 0975 254 102/1 M |
| Order No. | | 12503 |
| Description | | Profibus signal cable, molded on one side with M12 male connector, 5 poles, B coding, 1 meter, PUR jacket, halogen free, shielded, violet. |
| Note | | The application of these products in harsh environments should always be checked before use. |
| Color of housing | | black |
| Product characteristics | | Oil resistance, Drag chains, EMC resistance |
| Classification | | |
| Belden class | | Signal Cable |
| Belden brand | | Lumberg-Automation |
| Approvals | | |
| Approvals | | UL |
| Cable | | |
| Cable length | | 1 m |
| Cable number | | 254 |
| Cable description | | Bus cable ProfiBus |
| Color of jacket | | violet |
| Material of outer jacket | | PUR |
| Without halogens as in EN 50267-2-3 | | ✓ |
| shielded | | ✓ |
| welding spark proof | | ✗ |
| Outer diameter of the cable | | 7.6 mm |
| Number of conductors | | 2 |
| Cable design | | 2 x 0.38 mm ² |
| Conductor design | | 19 x 0.15 mm |
| Flame resistant according to standard | | IEC 60332-2, CSA FT-2 |