




**Product information**  
**0911 ANC 407 - 0911 ANC 407/10 M**  
**12822**

<b>Name</b>	
0911 ANC 407	
	
AS-Interface connector for direct connection to a wired male connector: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406 is included with the delivered product., 10 meter, PUR jacket, halogen free, black.	
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Type</b>	0911 ANC 407/10 M
<b>Order No.</b>	12822
<b>Description</b>	AS-Interface connector for direct connection to a wired male connector: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406 is included with the delivered product., 10 meter, PUR jacket, halogen free, black.
<b>Note</b>	The application of these products in harsh environments should always be checked before use.
<b>Color of housing</b>	orange
<b>Product characteristics</b>	Oil resistance, Vibration resistance
<b>Classification</b>	
<b>Belden class</b>	AS-Interface Direct Connectors
<b>Belden brand</b>	Lumberg-Automation
<b>Environmental conditions</b>	
<b>Degree of protection (IP), mounted</b>	IP67
<b>Materials</b>	
<b>Housing material / Molded body</b>	PA
<b>Contact bearer material</b>	PUR
<b>Electrical data</b>	
<b>Nominal current at 40°C</b>	2 A / contact
<b>Cable</b>	
<b>Cable length</b>	10 m
<b>Cable number</b>	41
<b>Cable description</b>	Bus cable
<b>Color of jacket</b>	orange
<b>Material of outer jacket</b>	PUR
<b>Without halogens as in EN 50267-2-3</b>	✘
<b>shielded</b>	✘
<b>welding spark proof</b>	✘
<b>Outer diameter of the cable</b>	7.2 mm
<b>Nominal diameter of the cable - amount</b>	2
<b>Nominal diameter of the cable - diameter</b>	1.50 mm <sup>2</sup>
<b>Diameter of conductor - Number</b>	192
<b>Diameter of conductor</b>	0.10 mm
<b>Flame resistant according to standard</b>	none