



Product information M12 Single Ended Cordsets -Stainless Steel Types - PRKWT4-07/5 M 13601

Name M12 Single Ended Cordsets - Stainless Steel Types Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Delivery informations Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance (Cassification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Delivery informations Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics (vibration resistance, Acids resistance Classification Eclass-ID (27260702 Bedden brand (Lumberg-Automation Eclass-ID (27260702 Bedgen of housing (Pub)-in contact (Pub)-in con	
Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Delivery informations Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Eclass - ID 27260702 Belden brand Lumberg-Automation Eclass - ID 27260702 Type of pluy-in contact Female connector Female connector Female connector Female connector	
Delivery informations Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing available Female connector Female connector Jensel connector Female connector Jensel connector	
Delivery informations Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing available Female connector Female connector Jensel connector Female connector Jensel connector	
Delivery informations Availability available Product description PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	screw in stainless steel -
Availability available Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon expecially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Type of plug-in contact Female connector Design of housing angled	
Product description Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Type PRKWT 4-07/5 M Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Eelden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Order No. 13601 Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Description Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon especially designed for use in food processing equipment – 4 poles, PVC jacket, 5 meters Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Number of contacts 4 Color of housing orange Product characteristics Vibration resistance, Acids resistance Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Type of plug-in contact Female connector Design of housing angled	screw in stainless steel _
Color of housing orange Product characteristics Vibration resistance, Acids resistance Classification Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Type of plug-in contact Female connector Design of housing angled	JOICH III JIAIIIIGGG JUCCI —
Product characteristics Vibration resistance, Acids resistance Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing angled	
Mechanical data Type of plug-in contact Female connector Design of housing angled	
Type of plug-in contact Female connector Design of housing angled	
Design of housing angled	
Thread M12	
Design of electrical connection screw connection	
Coding of the M12 round plug connector A	
LED display present X	
<mark>^"</mark>	
Environmental conditions	
Environmental temperature -25 °C 70 °C	
Degree of protection (IP), mounted IP67 / IP69K	
Pollution degree 3	
Materials Housing material (Maded body)	
Housing material / Molded body PVC	
Contact bearer material PVC	
Contact material CuSn	
Contact material - Surface refinement pre-nickeled and gold-plated	
Knurled screw / nut material stainless steel	
Sealing material EPDM	
Electrical data	
Contact resistance $\leq 5 \text{ m}\Omega$	
Rated current In 4 A at 40°C, UL and notice derating	
Nominal voltage 240 V	
Rated voltage (Value) 250 V	
Test voltage 2 kV eff./60 s	
Insulation resistance $> 1 \text{ G}\Omega$	
Approvals	
Approvals UL	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.