



Product information M12 Single Ended Cordsets -Stainless Steel Types - PRKWT5-56/5 M 13635

| Name                                   | M12 Single Ended Cordsets - Stainless Steel Types  |
|--|--|
|  |  |
|  | Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon screw in stainless steel |
| Delivery informations                  | especially designed for use in food processing equipment – 5 poles, PVC jacket, 5 meters   |
| Availability                           | available  |
| Product description                    | available  |
|  | PRKWT 5-56/5 M   |
| Type<br>Order No.                      | 13635  |
|  | Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon screw in stainless steel |
| Description                            | especially designed for use in food processing equipment – 5 poles, PVC jacket, 5 meters   |
| Number of contacts                     | 5  |
| Color of housing                       | orange   |
| Product characteristics                | Vibration resistance, Acids resistance   |
| Classification                         |  |
| Belden brand                           | Lumberg-Automation   |
| Eclass-ID                              | 27260702   |
| Mechanical data                        |  |
| Type of plug-in contact                | Female connector   |
| Design of housing                      | angled   |
| Thread                                 | M12  |
| Design of electrical connection        | screw connection   |
| Coding of the M12 round plug connector | A  |
| LED display present                    | X  |
| Environmental conditions               |  |
| Environmental temperature              | -25 °C 70 °C   |
| Degree of protection (IP), mounted     | IP67 / IP69K   |
| Pollution degree                       | 3  |
| Materials                              |  |
| Housing material / Molded body         | PVC  |
| Contact bearer material                | PVC  |
| Contact material                       | CuSn   |
| Contact material - Surface refinement  | pre-nickeled and gold-plated   |
| Knurled screw / nut material           | stainless steel  |
| Sealing material                       | EPDM EPDM  |
| Electrical data                        |  |
| Contact resistance                     | ≤5 mΩ  |
| Rated current In                       | 4 A at 40°C, UL and notice derating  |
| Nominal voltage                        | 60 V   |
| Rated voltage (Value)                  | 63 V   |
| Test voltage                           | 1.5 kV eff./60 s   |
| Insulation resistance                  | >1.6Ω  |
| Approvals                              |  |

The information published has been compiled as carrefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect