

A BELDEN BRAND

Product information 0911 ANC 410 - 0911 ANC 410/10 M 15932

Name	0911 ANC 410
	1
	AS-Interface connector for direct connection to two wired male connectors: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406 is included with the delivered product., 10 meter, PUR jacket, halogen free, black.
Delivery informations	is included with the delivered product, to meter, Por jacket, nalogen mee, black.
Availability	available
Product description	avairable
Туре	0911 ANC 410/10 M
Order No.	15932
Description	AS-Interface connector for direct connection to two wired male connectors: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406
Description	As-interface connector for direct connector for two wred male connectors, redsaule access technology to rec 60552-0. As-interface connector 0911 ANC 400 is included with the delivered product, 10 meter, PUR jacket, halogen free, black.
Note	The application of these products in harsh environments should always be checked before use.
Color of housing	orange
Product characteristics	Oil resistance, Vibration resistance
Classification	
Belden class	AS-Interface Direct Connectors
Belden brand	Lumberg-Automation
Environmental conditions	
Degree of protection (IP), mounted	IP67
Materials	
Housing material / Molded body	PA
Contact bearer material	PUR
Electrical data	
Nominal current at 40°C	2 A / contact
Cable	
Cable length	10 m
Cable number	41
Cable description	Bus cable
Color of jacket	orange
Material of outer jacket	PUR
Without halogens as in EN 50267-2-3	×
shielded	×
welding spark proof	×
Outer diameter of the cable	7.2 mm
Nominal diameter of the cable - amount	2
Nominal diameter of the cable - diameter	1.50 mm ²
Diameter of conductor - Number	192
Diameter of conductor	0.10 mm

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.