



## Product information RSW - RSW 30-01/5 M 15938

Name	RSW
Dell'esse tofour eller	Actuator/sensor cordset, 7/8" male connector, right angle version, with self-locking threaded joint and molded cable, PVC cable, orange, 3 poles, 5 meters.
Delivery informations	l available
Availability  Product description	available
Product description Type	RSW 30-01/5 M
Order No.	15938  Actuator/consor condect 7/8" male connector right angle version, with self-locking threaded joint and molded cable PMC cable orange 3 notes 5 meters
Description Number of contacts	Actuator/sensor cordset, 7/8" male connector, right angle version, with self-locking threaded joint and molded cable, PVC cable, orange, 3 poles, 5 meters.
Number of contacts	3
Color of housing Product characteristics	Orange
*****	Vibration resistance, Oil resistance
Mechanical data  Type of plug-in contact	Male connector
Design of housing	
<u> </u>	angled 7/8"
Thread  Design of electrical connection	connector 7/8 inch
LED display present	×
Environmental conditions	1000 0000
Environmental temperature	-40 °C 90 °C
Degree of protection (IP), mounted	IP68
Pollution degree	3
Materials Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	
	TPU, self-extinguishing
Contact material  Contact material - Surface refinement	CuZn
Knurled screw / nut material	silver-plated and 0.3 microns gold-plated  PA
	PA .
Electrical data Contact resistance	45.000
Rated current In	$\leq$ 5 m $\Omega$ 12 A at 40°C, UL and notice derating
	240 V
Nominal voltage	250 V
Rated voltage Test voltage	2 kV eff./60 s
Insulation resistance	2 κν eii./ου s > 1 GΩ
Approvals	/ I U3ε
RoHS 2002/95/EG compliant	RoHS 2002/95/EG
Cable	10.0 2020.0.20
Cable length	5 m
Cable number	01
Cable description	Cable for sensors and actuators
Color of jacket	orange
Material of outer jacket	PVC
Outer diameter of the cable	7.20 mm
Nominal diameter of the cable	
	3 x 0.75 mm <sup>2</sup>
Construction of conductor	22 x 0.2 mm

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respec




Flame resistant according to standard

none

Picture

Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.