




**Product information**  
**0911 ANC 410 - 0911 ANC 410/2 M**  
**15946**

0911 ANC 410	
Name	0911 ANC 410
	
	AS-Interface connector for direct connection to two wired male connectors: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406 is included with the delivered product., 2 meter, PUR jacket, halogen free, black.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Type	0911 ANC 410/2 M
Order No.	15946
Description	AS-Interface connector for direct connection to two wired male connectors: reusable access technology to IEC 60352-6. AS-Interface connector 0911 ANC 406 is included with the delivered product., 2 meter, PUR jacket, halogen free, black.
Note	The application of these products in harsh environments should always be checked before use.
Color of housing	orange
Product characteristics	Oil resistance, Vibration resistance
<b>Classification</b>	
Belden class	AS-Interface Direct Connectors
Belden brand	Lumberg-Automation
<b>Environmental conditions</b>	
Degree of protection (IP), mounted	IP67
<b>Materials</b>	
Housing material / Molded body	PA
Contact bearer material	PUR
<b>Electrical data</b>	
Nominal current at 40°C	2 A / contact
<b>Cable</b>	
Cable length	2 m
Cable number	41
Cable description	Bus cable
Color of jacket	orange
Material of outer jacket	PUR
Without halogens as in EN 50267-2-3	✘
shielded	✘
welding spark proof	✘
Outer diameter of the cable	7.2 mm
Nominal diameter of the cable - amount	2
Nominal diameter of the cable - diameter	1.50 mm <sup>2</sup>
Diameter of conductor - Number	192
Diameter of conductor	0.10 mm