




Product information
M12 Single Ended Cordsets - Standard Types, A and U coding - RST 5-228/10 M 17061

Name	
Name	M12 Single Ended Cordsets - Standard Types, A and U coding
	
	Actuator/sensor cordset, M12 male connector, straight version, with self-locking threaded joint and molded cable, 5 poles, PUR jacket, 10 meters
Delivery informations	
Availability	available
Product description	
Type	RST 5-228/10 M
Order No.	17061
Description	Actuator/sensor cordset, M12 male connector, straight version, with self-locking threaded joint and molded cable, 5 poles, PUR jacket, 10 meters
Number of contacts	5
Color of housing	black translucent
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Male connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	✘
Environmental conditions	
Environmental temperature	-25 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU
Contact bearer material	TPU
Contact material	CuSn
Contact material - Surface refinement	pre-nickeled and gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I _n	4 A at 40°C, UL and notice derating
Nominal voltage	60 V
Rated voltage (Value)	63 V
Test voltage	1.5 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.