




Product information
M12 Single Ended Cordsets - Stainless Steel Types -
PRKWT4-07/25 M
18028

Name	
Name	M12 Single Ended Cordsets - Stainless Steel Types
	
	Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon screw in stainless steel – especially designed for use in food processing equipment – 4 poles, PVC jacket, 25 meters
Delivery informations	
Availability	available
Product description	
Type	PRKWT 4-07/25 M
Order No.	18028
Description	Actuator/sensor cordset, M12 female connector, right angled version, with self-locking threaded joint and molded cable, hexagon screw in stainless steel – especially designed for use in food processing equipment – 4 poles, PVC jacket, 25 meters
Number of contacts	4
Color of housing	orange
Product characteristics	Vibration resistance, Acids resistance
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	angled
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	✘
Environmental conditions	
Environmental temperature	-25 °C ... 70 °C
Degree of protection (IP), mounted	IP67 / IP69K
Pollution degree	3
Materials	
Housing material / Molded body	PVC
Contact bearer material	PVC
Contact material	CuSn
Contact material - Surface refinement	pre-nickel and gold-plated
Knurled screw / nut material	stainless steel
Sealing material	EPDM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage (Value)	250 V
Test voltage	2 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.