



**Product information**  
**Field Attachable M12 Connectors -**  
**Stainless Steel Types -RSCN 4/7**  
**18319**

Name	
	<p><b>Field Attachable M12 Connectors - Stainless Steel Types</b></p> 
	M12 male connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food processing equipment –
Delivery informations	
Availability	available
Product description	
Type	RSCN 4/7
Order No.	18319
Description	M12 male connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food processing equipment –
Number of contacts	4
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Male connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	<b>✘</b>
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.75 mm <sup>2</sup>
connectable conductor cross-section multiple wire (with sleeve)	0.14 mm <sup>2</sup> mm <sup>2</sup>
Screw joint for cable for external cable diameter	3.0 mm ... 6.5 mm
Screwed cable gland, connecting thread	SW 15
Environmental conditions	
Environmental temperature	-25 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-coppered, CuSnZn
Knurled screw / nut material	stainless steel
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I <sub>n</sub>	4 A at 40°C, UL and notice derating
Nominal voltage	240 V

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



<b>Rated voltage (Value)</b>	250 V
<b>Test voltage</b>	2.0 kV eff./60 s
<b>Insulation resistance</b>	> 1 GΩ
<b>Approvals</b>	
<b>Approvals</b>	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.