



## Product information Field Attachable M12 Duo Connectors -RSCN 4/DUO 18323

Name	Field Attachable M12 Duo Connectors
	Field attachable Duo connector, for the connection of two cables (2 x 3 / 2 x 5), M12 male connector, straight version, with stainless steel hexagon threaded
	joint, assembling with screw terminals – especially designed for use in food processing equipment –
Delivery informations	
Availability	available
Product description	PCCN 4/DUO
Type Order No.	RSCN 4/DU0
Order No.	18323
Description	Field attachable Duo connector, for the connection of two cables (2 x 3 / 2 x 5), M12 male connector, straight version, with stainless steel hexagon threaded
Number of soutests	joint, assembling with screw terminals – especially designed for use in food processing equipment –
Number of contacts	
Color of housing	black
Classification Belden brand	Lumbar Automatica
	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	Mileseante
Type of plug-in contact	Male connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	X
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.75 mm <sup>2</sup>
Screw joint for cable for external cable diameter	3 mm 5 mm
Screwed cable gland, connecting thread	n/a
Environmental conditions	
Environmental temperature	-25 °C 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-coppered, CuSnZn
Knurled screw / nut material	stainless steel
Sealing material	FKM
Electrical data	
Contact resistance	$\leq 5 \text{ m}\Omega$
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage (Value)	250 V
Test voltage	2.0 kV eff./60 s
Insulation resistance	>1 6Ω

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respec