




Product information
0970 PSL 114
28335

Name	
0970 PSL 114	
	
Profibus-DP device with 8 digital inputs to connect standard sensors, combined FIXCON/M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.	
Delivery informations	
Availability	available
Product description	
Type	0970 PSL 114
Order No.	28335
Description	Profibus-DP device with 8 digital inputs to connect standard sensors, combined FIXCON/M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.
Note	The application of these products in harsh environments should always be checked before use.
Color of housing	orange
Product characteristics	Oil resistance, EMV resistance, Vibration resistance
Classification	
Belden class	I/O Modules with Digital Inputs (DI)
Belden brand	Lumberg-Automation
Mechanical data	
Weight	535 g
Dimensions (W x H x D)	60 mm x 179 mm x 51.3 mm
Environmental conditions	
Environmental temperature	0 °C ... 60 °C
Degree of protection (IP), mounted	IP67
Materials	
Housing material / Molded body	PUR
Approvals	
Approvals	UL
Bus system	
Fieldbus system	Profibus DP
Bus Connection	M12
Device Identification	044F hex
Transmission rate	12 MBd
Address range	1 dec. ... 126 dec.
Rotary address switches	1 dec. ... 99 dec.
Default address	99 dec.
System power supply	
System power supply	U _L
Nominal voltage (System power supply)	24 V DC
Voltage range DC (System power supply)	19 V ... 30 V
Power consumption (System power supply)	60 mA
Reverse polarity protection (System power supply)	Yes
Operating Indication (System power supply)	LED green
Sensors power supply	
Sensors power supply	U _S
Voltage range (Sensor power supply)	min. (U _L -1.5V)
Sensor current (at TU30°C) (Sensor power supply)	800 mA

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.




Short-circuit proof (Sensor power supply)	Yes
Indication (Sensor power supply)	LED green
Inputs	
Input wiring	Type 3 gem. IEC 61131-2
Signal type (Inputs)	Digital Inputs
Number of channels (Inputs)	8
Channel type (Inputs)	N.O., p-switching
Nominal input voltage	24 V DC
Voltage (Signal status "1") - Explanation	11 - 30 V
Voltage (Signal status "0") - Explanation	-3 - 5 V
Channel status indicator (Inputs)	LED yellow per channel
Input current at 24 V DC (typ.)	6 mA

Scope of delivery and accessories	
Scope of delivery	Dust covers M12 - 2 pieces, Attachable labels - 10 pieces

Picture

Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.