

a BELDEN BRAND

Product information 0975 254 101 - 0975 254 101/15 M 28406

| Name | 0975 254 101 |
|---------------------------------------|--|
| Name | 09/3/234 101 |
| | |
| | Profibus signal cable, molded on both sides with M12 male connector and M12 female connector, 5 poles, B coding, 15 meter, PUR jacket, halogen free, violet. |
| Delivery informations | available |
| Availability | available |
| Product description | 0975 254 101/15 M |
| Type | |
| Order No. | 28406 |
| Description | Profibus signal cable, molded on both sides with M12 male connector and M12 female connector, 5 poles, B coding, 15 meter, PUR jacket, halogen free, violet. |
| Note | The application of these products in harsh environments should always be checked before use. |
| Color of housing | black |
| Product characteristics | Oil resistance, Drag chains, EMC resistance |
| Classification | |
| Belden class | Signal Cable |
| Belden brand | Lumberg-Automation |
| Approvals | |
| Approvals | UL |
| Cable | |
| Cable length | 15 m |
| Cable number | 254 |
| Cable description | Bus cable ProfiBus |
| Color of jacket | violet |
| Material of outer jacket | PUR |
| Without halogens as in EN 50267-2-3 | ✓ |
| shielded | ✓ |
| welding spark proof | × |
| Outer diameter of the cable | 7.6 mm |
| Number of conductors | 2 |
| Cable design | 2 x 0.38 mm ² |
| Conductor design | 19 x 0.15 mm |
| Flame resistant according to standard | IEC 60332-2, CSA FT-2 |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.