



Product information Field Attachable M12 Connectors -Stainless Steel Types -RSCN 5/9 30546

Name	Field Attachable M12 Connectors - Stainless Steel Types
	M12 male connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food
Dalinam informations	processing equipment –
Delivery informations	a
Availability	available
Product description	DOON FIG
Type	RSCN 5/9
Order No.	30546
Description	M12 male connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food processing equipment –
Number of contacts	5
Color of housing	black
Classification Belden brand	Lumbara Automation
Eclass-ID	Lumberg-Automation
Mechanical data	27260702
Type of plug-in contact	Male appropria
·· · · ·	Male connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	X
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.75 mm ²
connectable conductor cross-section multiple wire (with sleeve)	0.14 mm ² mm ²
Screw joint for cable for external cable diameter	4.0 mm 8.0 mm
Screwed cable gland, connecting thread	SW 19
Environmental conditions	
Environmental temperature	-25 °C 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-coppered, CuSnZn
Knurled screw / nut material	stainless steel
Sealing material	FKM
Electrical data	
Contact resistance	≤5 mΩ
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	60 V



Rated voltage (Value)	63 V
Rated voltage (Value) Test voltage	1.5 kV eff./60 s
Insulation resistance	>1 6Ω
Approvals	
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.