



Product information M12 Single Ended Cordsets - Standard Types, A and Ucoding - RST 3-224/2 M 43703

Name	M12 Single Ended Cordsets - Standard Types, A and U coding
	Actuator/sensor cordset, M12 male connector, straight version, with self-locking threaded joint and molded cable, 3 poles, PUR jacket, 2 meters
Delivery informations	Actuator/sensor coruset, witz inale connector, straight version, with sen-locking unleaded joint and moded cable, s poles, non jacket, 2 meters
Availability	available
Product description	available
Туре	RST 3-224/2 M
Order No.	43703
Description	Actuator/sensor cordset, M12 male connector, straight version, with self-locking threaded joint and molded cable, 3 poles, PUR jacket, 2 meters
Number of contacts	3
Color of housing	black translucent
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Male connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	X
Environmental conditions	
Environmental temperature	-25 °C 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU
Contact bearer material	TPU
Contact material	CuSn
Contact material - Surface refinement	pre-nickeled and gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Electrical data	
Contact resistance	≤5 mΩ
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage (Value)	250 V
Test voltage	2.0 kV eff./60 s
Insulation resistance	>1 GΩ
Approvals	lui
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.