


**Product information**  
**Field Attachable M12 Connectors -**  
**Standard Type - RKCW8/9**  
**45006**

Name	
Field Attachable M12 Connectors - Standard Type	
	
	Field attachable connector, M12 female connector, right angled version, with threaded joint, assembling with screw terminals
Delivery informations	
Availability	available
Product description	
Type	RKCW 8/9
Order No.	45006
Description	Field attachable connector, M12 female connector, right angled version, with threaded joint, assembling with screw terminals
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	angled
LED display present	✗
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.50 mm <sup>2</sup>
Screw joint for cable for external cable diameter	4.0 mm ... 8.0 mm
Screwed cable gland, connecting thread	SW 19
Environmental conditions	
Environmental temperature	-25 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-nickeled and gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I <sub>n</sub>	2 A at 40°C, UL and notice derating
Nominal voltage	30 V
Rated voltage (Value)	36 V
Test voltage	0.9 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.