


Product information
0975 254 104 - 0975 254 104/5 M
47938

Name		0975 254 104
		
	Profibus signal cable, molded/assembled on both sides with M12 female connector, 5 poles, B coding and SUBD male connector, 9 poles, with switch-on terminating resistor, 5 meter, PUR jacket, halogen free, violet.	
Delivery informations		
Availability	available	
Product description		
Type	0975 254 104/5 M	
Order No.	47938	
Description	Profibus signal cable, molded/assembled on both sides with M12 female connector, 5 poles, B coding and SUBD male connector, 9 poles, with switch-on terminating resistor, 5 meter, PUR jacket, halogen free, violet.	
Note	The application of these products in harsh environments should always be checked before use.	
Product characteristics	Drag chains, EMC resistance	
Classification		
Belden class	Signal Cable	
Belden brand	Lumberg-Automation	
Approvals		
Approvals	UL	
Cable		
Cable length	5 m	
Cable number	254	
Cable description	Bus cable Profibus	
Color of jacket	violet	
Material of outer jacket	PUR	
Without halogens as in EN 50267-2-3	✓	
shielded	✓	
welding spark proof	✗	
Outer diameter of the cable	7.6 mm	
Number of conductors	2	
Cable design	2 x 0.38 mm ²	
Conductor design	19 x 0.15 mm	
Flame resistant according to standard	IEC 60332-2, CSA FT-2	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.