




Product information

**0975 254 105 - 0975 254 105/1 M
49255**

Name	
0975 254 105	
Profibus signal cable, molded/assembled on both sides with M12 male connector, 5 poles, B coding and SUBD male connector, 9 poles, with switch-on terminating resistor, 1 meter, PUR jacket, halogen free, violet.	
Delivery informations	
Availability	available
Product description	
Type	0975 254 105/1 M
Order No.	49255
Description	Profibus signal cable, molded/assembled on both sides with M12 male connector, 5 poles, B coding and SUBD male connector, 9 poles, with switch-on terminating resistor, 1 meter, PUR jacket, halogen free, violet.
Note	The application of these products in harsh environments should always be checked before use.
Product characteristics	Drag chains, EMC resistance
Classification	
Belden class	Signal Cable
Belden brand	Lumberg-Automation
Approvals	
Approvals	UL
Cable	
Cable length	1 m
Cable number	254
Cable description	Bus cable Profibus
Color of jacket	violet
Material of outer jacket	PUR
Without halogens as in EN 50267-2-3	✓
shielded	✓
welding spark proof	✗
Outer diameter of the cable	7.6 mm
Number of conductors	2
Cable design	2 x 0.38 mm ²
Conductor design	19 x 0.15 mm
Flame resistant according to standard	IEC 60332-2, CSA FT-2