



Product information
Field Attachable M12 Connectors -
Stainless Steel Types -RKCN 8/9
51351

Name	
Field Attachable M12 Connectors - Stainless Steel Types	
	
M12 female connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food processing equipment –	
Delivery informations	
Availability	available
Product description	
Type	RKCN 8/9
Order No.	51351
Description	M12 female connector, straight version, with stainless steel hexagon threaded joint, assembling with screw terminals – especially designed for use in food processing equipment –
Number of contacts	8
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	straight
Thread	M12
Design of electrical connection	screw connection
Coding of the M12 round plug connector	A
LED display present	✘
Connectable conductor cross-section multiple wire (without sleeve)	max. 0.50 mm ²
connectable conductor cross-section multiple wire (with sleeve)	0.14 mm ² mm ²
Screw joint for cable for external cable diameter	4.0 mm ... 8.0 mm
Screwed cable gland, connecting thread	SW 19
Environmental conditions	
Environmental temperature	-25 °C ... 85 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-nickeled and gold-plated
Knurled screw / nut material	stainless steel
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I _n	2 A at 40°C, UL and notice derating
Nominal voltage	30 V

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.