



## Product information Field Attachable M12 Connectors with spring-type terminals - RKCQ 4/7 58836

Name	Field Attachable M12 Connectors with spring-type terminals
	Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with spring-type terminals.
Delivery informations	
Availability	available
Product description	
Туре	RKCQ 4/7
Order No.	58836
Description	Field attachable connector, M12 female connector, straight version, with threaded joint, assembling with spring-type terminals.
Number of contacts	4
Color of housing	black
Classification	
Belden brand	Lumberg-Automation
Eclass-ID	27260702
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	straight
Thread	M12
Design of electrical connection	spring type terminal connection
Coding of the M12 round plug connector	A
LED display present	×
Connectable conductor cross-section multiple wire	max. 0.5 mm <sup>2</sup>
(without sleeve)	
Screw joint for cable for external cable diameter	3.0 mm 6.5 mm
Screwed cable gland, connecting thread	SW 15
Environmental conditions	0500 0000
Environmental temperature	-25 °C 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	DOT
Housing material / Molded body	PBT
Contact bearer material	PBT Strictles and the strictles are the strictles and the strictles are the strictle
Contact material	stainless steel
Contact material - Surface refinement	silver-plated and gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤5 mΩ
Rated current In	4 A at 40°C, UL and notice derating
Nominal voltage	250 V
Rated voltage (Value)	250 V
Test voltage	2 kV eff./60 s
Insulation resistance	>1 GΩ

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.