




Product information
ASB 4/LED 5-4-328/... M - ASB 4/LED
5-4-328/10 M
60643

| | |
|---------------------------------------|--|
| Name | |
| Name | ASB 4/LED 5-4-328/... M |
| Image |  <p>Image similar Abb. ähnlich</p> |
| Description | Actuator/sensor distribution box, 4-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 10 meter. |
| Delivery informations | |
| Availability | available |
| Product description | |
| Type | ASB 4/LED 5-4-328/10 M |
| Order No. | 60643 |
| Description | Actuator/sensor distribution box, 4-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, fixed connection cable, PUR jacket, halogen-free, black, 10 meter. |
| Number of contacts | 4 (M12) |
| Version | 4 ports |
| Color of housing | orange |
| Product characteristics | Vibration resistance, Oil resistance, Drag chains suitable |
| Classification | |
| Belden brand | Lumberg-Automation |
| Mechanical data | |
| Thread | M12 |
| LED display present | ✓ |
| Environmental conditions | |
| Environmental temperature | -15 °C ... 80 °C |
| Degree of protection (IP), mounted | IP67 |
| Pollution degree | 3 |
| Materials | |
| Housing material / Molded body | TPU, self-extinguishing |
| Contact bearer material | PA-GF, self-extinguishing |
| Contact material | CuZn (M12) |
| Contact material - Surface refinement | pre-nickel and 0.8 microns gold-plated |
| Knurled screw / nut material | CuZn, nickel-plated |
| Sealing material | FKM |
| Electrical data | |
| Contact resistance | ≤ 5 mΩ |
| Rated current In | 4 A per socket / 12 A max. at 40°C |
| Nominal voltage | 10 - 30 V DC |
| Rated voltage | 32 V |
| Insulation resistance | > 1 GΩ |
| Approvals | |
| Approvals | cURus |
| Cable | |
| Cable length | 10 m |
| Cable number | 328 |
| Cable description | Control cable |
| Color of jacket | black |
| Material of outer jacket | PUR |
| Outer diameter of the cable | 6.8 mm |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



| | |
|---------------------------------------|--|
| Number of conductors | 7 |
| Cable design | 4 x 0.34 mm ² + 3 x 0.75 mm ² |
| Flame resistant according to standard | IEC 60332-2, CSA FT-2 |
| Scope of delivery and accessories | |
| Scope of delivery | ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels |

Picture

Drawing

