


**Product information**  
**RSWU 12-ASB 8/LED 5-4-331/5M**  
**60720**

Name	
RSWU 12-ASB 8/LED 5-4-331/5M	
	
Actuator/sensor distribution box, 8-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, integrated control cable with M23 male right angle connector, 12 poles - suitable to connect at e2c 67 I/O modules 0942 UEM 027, 0942 UEM 014 and 0942 UEM 204 -	
Delivery informations	
Availability	available
Product description	
Type	RSWU 12-ASB 8/LED 5-4-331/5M
Order No.	60720
Description	Actuator/sensor distribution box, 8-port version, with LED operation and function indicators, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, integrated control cable with M23 male right angle connector, 12 poles - suitable to connect at e2c 67 I/O modules 0942 UEM 027, 0942 UEM 014 and 0942 UEM 204 -
Number of contacts	4 (M12)
Version	8 ports
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Mechanical data	
Thread	M12
LED display present	✓
Environmental conditions	
Environmental temperature	-15 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	PBT
Contact material	CuZn
Contact material - Surface refinement	pre-nickel and 0.8 microns gold-plated
Contact bearer material, side 2	PA-GF, self-extinguishing
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A per socket / 8 A max. at 40°C
Nominal voltage	10 - 30 V DC
Rated voltage	32 V
Insulation resistance	> 1 GΩ
Approvals	
Approvals	cURus
Cable	
Cable length	5 m
Cable number	331

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Cable description	Control cable
Color of jacket	black
Material of outer jacket	PUR
Outer diameter of the cable	8 mm
Number of conductors	11
Cable design	8 x 0.34 mm <sup>2</sup> + 3 x 0.75 mm <sup>2</sup>
Flame resistant according to standard	IEC 60332-2, CSA FT-2
Scope of delivery and accessories	
Scope of delivery	ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels

[Picture](#)

[Drawing](#)

